

# Construction Bridge Debris Containment



## **Debris Containment**

- InCord debris netting can wrap a bridge into a cocoon for safety, protecting workers, on-the-street pedestrians, and adjacent properties.
- Durable and reusable debris netting is available in single panel or stacked configurations under the brand name RocBloc™ with various mesh size and strengths to meet your exact job requirements.
- Debris netting may be combined with structural netting as a backing for greater strength in applications requiring heavy debris containment.
- Our netting ensures unrestricted work site access and traffic flow. For bridge containment nets, safety engineering and construction managers look to InCord for custom solutions.
- InCord safety netting complies with OSHA regulations and meets CPAI-84, Section 6, Tent Walls and Tops.



## **Personnel Safety**

- InCord bridge safety netting can provide personnel fall protection and debris protection, all in one system. Debris liners can be combined with Personnel Safety Nets for increased job site fall protection as well as for debris containment.
- Structural and personnel safety nets are made of high tenacity synthetic mesh designed to meet your most rigorous construction demands and tested to meet or exceed ANSI A10.11-1989.



# InCord Bridge Safety Netting Provides Protection for personnel and the public – all in one system.



Heavy duty safety nets offer fall protection for bridge construction workers while debris containment liners keep traffic passing below safe from falling objects during bridge construction.



N-820H structural netting with WS70 liner.



12 cubic feet of concrete caught by safety netting with debris liner.






Hoover Dam Bypass Project US 93

Netting Specifications for N-820H	
Style:	Raschel Knotless Netting
Fiber .....	High Tenacity, Polypropylene (HTPP)
Cord Diameter ....	3/16 inch (5 mm)
Mesh Size.....	2-1/2 inch (60 mm) square opening
Load Test, Max ...	6000 lb (2700 kg)
Weight .....	0.0528 lb/ft <sup>2</sup> (258 g/m <sup>2</sup> )
Melting Point.....	320°F (160°C)
UV.....	Extra UV Stabilizers added
Color.....	Black



## Debris Liners

	
WS70* 1/16" Knitted Polypropylene	WS50 1/8" Knitted Polypropylene
	Debris liners are available in roll form with selvage edge or in tarp configurations with a web border and grommets.
DNR900* 3/8" Knitted Polyester	*Order with suffix (FR) for flame-retardant treated liners conforming to NFPA-701.



Call InCord for all your netting needs at 1-800-596-1066



**InCord**

226 Upton Road  
Colchester, CT 06415

Phone: 860-537-1414 • Fax: 860-537-7393  
www.InCord.com • netting@InCord.com



InCord is an ISO 9001 registered company  
CAGE Code No. 1NPR7

**INCORD**