

Construction

Scaffold & Debris Nets



Where there's construction, there's debris –falling or flying objects that can seriously injure people and severely damage property if not for the safeguard of protective netting.

Construction netting consisting of scaffold wind/sun block and vertical debris nets can wrap a building in safety, protecting workers, pedestrians, and nearby structures from harm of falling material.

InCord scaffold and debris netting, a standard in the industry, is available in small mesh size for wind and sun bloc to 3/8 inch heavy strength mesh. Debris netting may be used in a stacked configuration or used as a liner in combination with structural netting such as personnel safety nets.

Our scaffold and debris nets are ultra-durable, reusable, and can be moved from floor to floor. Our scaffold netting complies with OSHA regulations and meets CPAI-84, Section 6, Tent Walls and Tops.



We can provide you with in-stock netting or custom netting.

Scaffold and Debris Nets improve productivity and reduces downtime from accidents and clean up.



Specifications and Sizes

Model	Material	Color	Thickness inch	Weft holes/inch	Warp holes/inch	Opacity	Ball Burst ASTM D3787	Weight oz/sq yd	FR Rating	Tarp Sizes	Roll Goods
WS85	knit polyester	white green	0.0475	9.75	11.75	85%	500 lb	13.70	NFPA-701 ¹	custom	8' 4" x 150'
WS85	knit polyester	sand	0.0325	9.75	11.75	85%	209 lb	5.18	NFPA-701 ¹	custom	6' x 150'
WS70 BK HDPE	high density polyethylene	black	0.0450	5.00	7.50	70%	312 lb	5.1	no	custom	max. width 16 ft (5 m) max. length 164 ft (50 m)
WS70 WH WS70 GN HDPE	high density polyethylene	white green	0.0350	5.00	7.50	70%	198 lb	2.40	no	custom	8' x 150' wh, gn 8.5' x 150' wh 10' x 300' gn
WS70 PP	polypropylene	black	0.0350	5.00	7.50	70%	341 lb	6.40	no	PSN	--
WS70 FR	polyethylene	black ²	0.0350	5.00	7.50	70%	177 lb	2.80	NFPA-701	custom	8' x 150' 8' 6" x 150'
Model	Material	Color	Thickness inch	Mesh Size	Breaking Strength ASTM D5034 Warp (1 inch grab) Weft		Weight oz/sq yd	FR Rating	Tarp Sizes	Roll Goods	
DNR18	PVC coated polyester	orange	0.0185	1/8 x 3/16 inch	179 lb	94 lb	5.90	NFPA-701	custom	4' x 150' 5' 6" x 150' 8' x 150' 8' 6" x 150'	
DNR75	knit polyethylene	black	0.035	5/16 inch	87.7 lb	66.4 lb	3.40	no	custom	4' x 150' 8.5' x 150' 10' 6" x 150'	
DNR75 FR	knit polyethylene	orange blue	0035	5/16 inch	87.7 lb	66.4 lb	3.40	NFPA-701	custom	4' x 150' 5' 6" x 150' 8.5' x 150' 10' 6" x 150'	
Model	Material	Color ³	Thickness inch	Mesh Size	Breaking Strength ASTM D5034 Warp (1 inch grab) Weft		Weight oz/sq yd	FR Rating	Tarp Sizes	Roll Goods	
DNR800	knit polyester	white	0.043	3/8 inch	233	79	8.0	NFPA-701	custom	10' x 300'	
DNR900	knit polyester	black	0.043	3/8 inch	233	79	8.0	NFPA-701	custom	10' x 300'	


1. FR version available on special order 2. Available Colors: black, white, green. 3. Std. Colors: sand, merlot, green, white, gray, black – custom colors available.

Debris liners are available in roll form with selvage edge or in tarp configurations with a web border and grommets.

Please note that we specialize in custom netting, call for a quotation on other sizes.




RPY13AN



WS50



WS70



DNR18



DNR75



DNR800 / DNR900

Call InCord for all your netting needs at 1-800-596-1066



InCord

226 Upton Road
Colchester, CT 06415

Phone: 860-537-1414 • Fax: 860-537-7393
www.InCord.com • netting@InCord.com



InCord is an ISO 9001
registered company

CAGE Code No. 1NPR7

INCORD